



MUSIS



Silverline (120)

Dichiarazione di Conformità CE

Direttiva 89/106/CEE



Avorio (036700001)



1200 x 200mm

Miele (036700020)



1200 x 200mm

Nocciola (036700002)



1200 x 200mm



Formato

| Size | Format | Formate | pz | m ² | kg | box | m ² | kg |
|--------|--------|---------|----|----------------|------|-----|----------------|------|
| 20x120 | | | 6 | 1.44 | 32.9 | 36 | 51.84 | 1185 |

The undersigned Luigi Toni, as Legal Representative of Musis Ceramica brand, that belongs to Gruppo Armonie S.p.A., via Statale 467, n° 136 42013 Casalgrande (REGGIO EMILIA) and regarding the product unit code number 90027500,

DECLARES

that the following construction product:

| | |
|---|--|
| Type | Dry pressed ceramic tiles - gres porcelain stoneware - Group BIa - GL |
| Series – Group of product | 120 30x120. 20x120. 15x120. 30x180. 20x180 |
| Description and intended use of product | Ceramic Tiles Internal and External Floorings Ceramic Tiles for Internal and External Wall Finishes |
| Note | Tiles not used in suspended ceilings |

is conform with the relevant requirement of the Construction Product Directive Council (Directive 89/106/CE) and that the following standards have been applied:

- Annex/s ZA ZB - EN 14411 "Ceramic tiles – Definition, classification, characteristic and marking".

Provisions to which the product conforms:

| CHARACTERISTICS | STANDARDS APPLIED/ METHOD OF TEST | VALORE DICHIARATO |
|--|--------------------------------------|---|
| Reaction to fire | Decision 96/603/CEE as amended | A1 _n |
| Water absorption | EN ISO 10545-3 | ≤0,5% |
| Slipperiness | B.C.R.A. (D.M. 236/89) | > 0,40 |
| Bending strength | EN ISO 10545-4 | S >700 N for thickness < 7,5 mm R >35 N/mm ² for thickness < 7,5 mm S >1300 N for thickness ≥ 7,5 mm R >35 N/mm ² for thickness ≥ 7,5 mm |
| Thermal shock resistance | EN ISO 10545-9 | Resistant |
| Durability: Frost resistance | EN ISO 10545-12 | Resistant |
| Resistance to low concentration of acids and alkalis | EN ISO 10545-13 | Resistant |
| Resistance to high concentration of acids and alkalis | | Resistant |
| Resistance to household chemicals and swimmingpool salts | | Compliant |
| Stain resistance | EN ISO 10545-14 | Class 5 |
| (*) Pb release | EN ISO 10545-15 | < 0,8 mg/dm ² |
| (*) Cd release | EN ISO 10545-15 | < 0,07 mg/dm ² |

(*) test conducted by the Notified Body AECC Agenzia Europea Certificazione Costruzioni UE number 1596

Luigi Toni

(Legal Representative - Gruppo Armonie S.p.A.)



MUSIC



- Natural essence of oak
- Soft designs with light color variations
- Contemporary design which brings elegant simplicity both to domestic environment and to commercial areas.
- Anti-slip finish for a sense of continuity between indoor and outdoor
- Premium Quality: Mass stoneware UNI EN 14411 - G Bla